



WEINTEK

HMI Comparison iP - IE - cMTX Series

Feature		MT8000iP	MT8000iE	Basic cMT1000X	Standard cMT2000X	Advanced cMT3000X	Headless cMT- FHDX	Headless cMT- SVRX	
Weincloud	Dashboard			Optional					
	EasyAccess 2.0 ¹			Optional					
Function	64-bit Data Type			•	•	•	•	•	
	3G/4G Dongle	•	•	•	•	•	•	•	
	USB Tethering	•	•	•	•	•	•	•	
	Web Interface (EasyWeb 2.0)			•	•	•	•	•	
	Secure Communication			•	•	•	•	•	
	Email		•	•	•	•	•	•	
	FTP Server	•	•	•	•	•	•	•	
	String Table		•	•	•	•	•	•	
	Ethernet Printer			•	•	•	•	•	
	Time Synchronization (NTP)		•	•	•	•	•	•	
	Web Streaming				•	•	•	•	
	Window Animation / Transparency				•	•	•	•	
	LDAP				•	•	•	•	
	WebView				•	•	•	•	
	cMT Viewer App				•	•	•	•	
	cMT Diagnoser			•	•	•	•	•	
	VNC Server	•	•	•	•	•	•	•	
	Object	VNC Viewer		•	•	•	•	•	•
		PDF Reader			•	•	•	•	•
BACnet Schedule				•	•	•	•	•	
Condition Object					•	•	•	•	
Action Trigger					•	•	•	•	
Media Player					•	•	•	•	
IP/USB Camera					•	•	•	•	
JS Object/JS Action					•	•	•	•	
Event Bar Chart						•	•	•	
PLC Web Browser					•	•	•		
IIoT/Energy	Barcode Scanner (Android Camera)					•	•	•	
	MQTT Cloud Service Integration ²				•	•	•	•	
	MQTT		•	•	•	•	•	•	
	OPC UA Client	•	•	•	•	•	•	•	
	OPC UA Server					•	Optional	•	
	Database Server					•	•	•	
Driver	SQL Query					•	•	•	
	Energy Demand Display / Setting					•	•	•	
	SIEMENS MPI ³	•	•	•	•	•	•	•	
Others	CAN bus					•	•	•	
	CODESYS® ⁴				•	•	•	•	

*1.EasyAccess2.0 license is required and needs to be purchased separately. An exception is cMT-SVRX-822 which has built-in license.

*2. Integrated with AWS IoT, Sparkplug B, Azure IoT Hub, Google Cloud IoT Core.

*3. For the standard models cMT2108X2 and cMT2158X, only the cMT2108X2(V2) and cMT2158X (V2) versions support MPI.

*4. CODESYS® license is required and needs to be purchased separately. CODESYS® is not supported on cMT2166X (cMT X Standard).

*For more software differences, please see the EasyBuilder Pro User Manual Appendix A.

* CODESYS® is a trademark of CODESYS GmbH.